

Cross-reference guide: Armstrong, B&G and TACO to Grundfos

Manufacturer	Model	Port-to-port length	Flange size	Grundfos model	Port-to-port length	Flange size	
Armstrong	ARMflo E21	8-1/2"	1-1/2"	UP43-110F	8-1/2"	1-1/2"	
	ARMflo E23	8-1/2"	1-1/2"	UP43-110F	8-1/2"	1-1/2"	
	S 45	10"	2-1/2", 3"	UP53-45F*	9-7/8"	2", 2-1/2", 3"	
	S 46	10"	2-1/2", 3"	UP53-46F*	9-7/8"	2", 2-1/2", 3"	
	S 55	12"	3"	UPS53-55/57F*	11-7/8"	2", 2-1/2", 3"	
	S 57	12"	3"	UPS53-55/57F*	11-7/8"	2", 2-1/2", 3"	
	S 69	14-1/4"	3"	UPS75-69F*	14"	2", 2-1/2", 3"	
	H51	11-1/2"	1"	UPS32-80/2*□	11"	3/4" to 1-1/2"	
	H52	11-1/2"	1"	UPS32-80*□	11"	3/4" to 1-1/2"	
	H53	11-1/2"	1-1/2"	UPS40-160/2*	11-1/2"	1-1/2"	
	H54	11-1/2"	2"	UPS50-80/2*	11-1/2"	2"	
	H63	13-1/2"	1-1/2"	UPS32-160/2*	13-1/2"	1-1/2"	
	H64	13-1/2"	1-1/2"	UPS32-160/2*	13-1/2"	1-1/2"	
	H65	13-1/2"	1-1/2"	UPS40-240/2*	13-1/2"	1-1/2"	
	H66	14"	2"	UPS50-160/2*	14"	2"	
	H67	14"	2"	UPS50-160/2*	14"	2"	
	H68	14"	2"	UPS50-240/2*	14"	2"	
	1050 1B (1/4HP)	11-1/2"	1"	UPS32-80/2*□	11"	3/4" to 1-1/2"	
	1050 1-1/4B (1/4HP)	11-1/2"	1-1/4"	UPS32-80/2*□	11"	3/4" to 1-1/2"	
	1050 1-1/2B (1/4HP)	11-1/2"	1-1/2"	UPS32-80/2*□	11"	3/4" to 1-1/2"	
	1050 2B (1/3HP)	11-1/2"	2"	UPS50-80/4*	11-1/2"	2"	
	1050 2B (1/2HP)	11-1/2"	2"	UPS50-80/4*	11-1/2"	2"	
	1050 2B (3/4HP)	11-1/2"	2"	UPS50-80/4*	11-1/2"	2"	
	1060 1-1/2 D (1/2HP)	13-1/2"	1-1/2"	UPS32-160/2*	13-1/2"	1-1/2"	
	1060 1-1/2 D (3/4HP)	13-1/2"	1-1/2"	UPS32-160/2*	13-1/2"	1-1/2"	
	1060 1-1/2 D (1-1/2HP)	13-1/2"	1-1/2"	UPS40-240/2*	13-1/2"	1-1/2"	
	1060 2D (3/4HP)	14"	2"	UPS50-160/2*	14"	2"	
	1060 2D (1HP)	14"	2"	UPS50-160/2*	14"	2"	
	1060 2D (1-1/2HP)	14"	2"	UPS50-160/2*	14"	2"	
	1060 2D (2HP)	14"	2"	UPS50-240/2*	14"	2"	
	TACO	120	11"	2"	UPS32-40/4*□	11"	3/4" to 1-1/2"
		131	13-5/8"	3"	UP53-45F*□	10"	2", 2-1/2", 3"
133		13-5/8"	3"	UPS53-55/57*□	11-7/8"	2", 2-1/2", 3"	
1600		10-1/4"	1-1/2"	UPS32-80/2*	11"	1-1/2"	
1610		10-1/4"	1-1/2"	UPS32-80/2*	11"	1-1/2"	
1612		13-1/2"	1-1/2"	UPS32-160/2*	13-1/2"	1-1/2"	
1614		13-1/2"	1-1/2"	UPS32-160/2*	13-1/2"	1-1/2"	
1616		14-1/2"	2"	UPS40-240/2*□	13-1/2"	1-1/2"	
1630		13-1/2"	2"	UPS50-80/4*□	11-1/2"	2"	
1632		13-1/2"	2"	UPS50-160/2*	14"	2"	
1634		13-1/2"	2"	UPS50-160/2*	14"	2"	
1636		16-1/2"	2"	UPS50-240/2*□	14"	2"	
1638		16-1/2"	2"	UPS50-240/2*□	14"	2"	

★ Bronze version to be used in open systems.

□ Replacement model requires piping and/or flange modification.

Disclaimer: This cross-reference is a guide only. Use individual technical data sheets for correct comparison.

Cross-reference guide

Manufacturer	Model	Port-to-port length	Flange size	Grundfos model	Port-to-port length	Flange size
B&G	2-1/2"	10"	2-1/2"	UP53-45F*	9-7/8"	2", 2.5", 3"
	LD3	10"	3"	UP53-45F*	9-7/8"	2", 2.5", 3"
	HD3	10"	3"	UP53-46F*	9-7/8"	2", 2.5", 3"
	PD-35	12"	3"	UPS53-55/57F*	11-7/8"	2", 2.5", 3"
	PD-37	12"	3"	UPS53-55/57F*	11-7/8"	2", 2.5", 3"
	PD-38	14-1/2"	3"	UPS75-69F*	14"	2", 2.5", 3"
	PD-40	14-1/2"	3"	UPS50-160/2*□	14"	2"
	601	11"	1"	UPS32-80/2*	11"	3/4" to 1-1/2"
	602	11"	1"	UPS32-80/2*	11"	3/4" to 1-1/2"
	603	11"	1"	UPS50-80/2*□	11-1/2"	2"
	604	11"	1-1/4"	UPS32-80/2*	11"	3/4" to 1-1/2"
	609	11-1/2"	1-1/2"	UPS40-160/2*	11-1/2"	1-1/2"
	610	11-1/2"	2"	UPS50-80/4*	11-1/2"	2"
	621	13-1/2"	2"	UPS40-80/4	13-1/2"	1-1/2"
	614	13-1/2"	1-1/2"	UPS40-240/2	13-1/2"	1-1/2"
	615	13-1/2"	2"	UPS50-160/2	14"	2"
	616	13-1/2"	2"	UPS50-160/2	14"	2"
	622	13-1/2"	1-1/2"	UPS32-160/2	13-1/2"	1-1/2"
	623	13-1/2"	1-1/2"	UPS40-240/2	13-1/2"	1-1/2"
	617	13-1/2"	1-1/2"	UPS40-240/2	13-1/2"	1-1/2"
	624	14"	2"	UPS50-160/2	14"	2"
	625	14"	2"	UPS50-240/2	14"	2"
	60-11	11"	1-1/4"	UPS32-80/2*	11"	3/4" to 1-1/2"
	60-13	11-1/2"	1-1/2"	UPS40-160/2*	11-1/2"	1-1/2"
	60-14	11-1/2"	2"	UPS50-80/2*	11-1/2"	2"
	60-15	13-1/2"	1-1/2"	UPS32-160/2	13-1/2"	1-1/2"
	60-16	13-1/2"	1-1/2"	UPS32-160/2	13-1/2"	1-1/2"
	60-17	13-1/2"	1-1/2"	UPS40-240/2	13-1/2"	1-1/2"
60-19	14"	2"	UPS50-160/2	14"	2"	
60-20	14"	2"	UPS50-160/2	14"	2"	
60-21	14"	2"	UPS50-240/2	14"	2"	

★ Bronze version to be used in open systems.

□ Replacement model requires piping and/or flange modification.

Disclaimer: This cross-reference is a guide only. Use individual technical data sheets for correct comparison.

UPS range

Pump type	Voltage [V]					Poles	
	1 x 115	1 x 230	3 x 208-230	3 x 460	3 x 575★	2	4
UPS 32-40 F	●	●	●	●	●		●
UPS 32-80 F	●	●	●	●	●	●	
UPS 32-160 F	●	●	●	●	●	●	
UPS 40-40 F	●	●	●	●	●		●
UPS 40-80/2 F	●	●	●	●	●	●	
UPS 40-80/4 F	●	●	●	●	●		●
UPS 40-160 F	●	●	●	●	●	●	
UPS 40-240 F	●	●	●	●	●	●	
UPS 50-40 F	●	●	●	●	●		●
UPS 50-80/2 F	●	●	●	●	●	●	
UPS 50-80/4 F	●	●	●	●	●		●
UPS 50-160 F		●	●	●	●	●	
UPS 50-240 F			●	●	●	●	
UPS 53-55/57 F	●	●	●	●	●	●	
UPS 75-69 F		●	●	●	●	●	
UPS 80-40 F			●	●	●		●
UPS 80-80 F			●				●
UPS 80-160 F			●	●	●	●	
UPS 100-40 F			●	●	●		●

★Canada only

UP range

Pump type	Voltage [V]	Poles	
	1 x 115/230 V	2	4
UP 43-70 F	●	●	
UP 43-110 F	●	●	
UP 53-45 F	●	●	
UP 53-46 F	●	●	

Pump overview

Model	Flow U.S. GPM	Head feet	PH	Max. rpm	Flange	Flange type
UP 43-70F	15-100	1-23	1	3450	1 1/2" non ANSI 2 bolt w/ (2) 1/2" dia. holes	GF 40/43
UP 43-110F	15-105	1-37	1	3450	1 1/2" non ANSI 2 bolt w/ (2) 1/2" dia. holes	GF 40/43
UP 53-45 F	15-100	1-23	1	3450	2", 2 1/2", 3" non ANSI 4 bolt w/ (4) 5/8" dia. holes	GF 53
UP 53-46 F	15-105	1-37	1	3450	2", 2 1/2", 3" non ANSI 4 bolt w/ (4) 5/8" dia. holes	GF 53
UPS 32-40/4	9-52	1-11	1-3	1750	1 1/4" non ANSI 4 bolt w/ (4) 5/8" dia. holes	GF 15/26
UPS 32-80/2	9-67	1-25	1-3	3450	1 1/4" non ANSI 2 bolt w/ (2) 1/2" dia. holes	GF 15/26
UPS 32-160/2	9-76	1-45	1-3	3450	1 1/2" non ANSI 2 bolt w/ (2) 1/2" dia. holes	GF 40/43
UPS 40-40/4	13-85	1-11	1-3	1750	1 1/2" non ANSI 2 bolt w/ (2) 1/2" dia. holes	GF 40/43
UPS 40-80/2	13-105	1-30	1-3	3450	1 1/2" non ANSI 2 bolt w/ (2) 1/2" dia. holes	GF 40/43
UPS 40-80/4	13-120	1-25	1-3	1750	1 1/2" non ANSI 2 bolt w/ (2) 1/2" dia. holes	GF 40/43
UPS 40-160/2	13-110	1-46	1-3	3450	1 1/2" non ANSI 2 bolt w/ (2) 1/2" dia. holes	GF 40/43
UPS 40-240/2	13-130	1-62	1-3	3450	1 1/2" non ANSI 2 bolt w/ (2) 1/2" dia. holes	GF 40/43
UPS 50-40/4	20-125	1-12	1-3	1750	2" non ANSI 4 bolt w/ (4) 9/16" dia. holes	GF 50
UPS 50-80/4	20-160	1-24	1-3	1750	2" non ANSI 4 bolt w/ (4) 9/16" dia. holes	GF 50
UPS 50-80/2	20-150	1-30	1-3	3450	2" non ANSI 4 bolt w/ (4) 9/16" dia. holes	GF 50
UPS 50-160/2	20-170	1-46	1-3	3450	2" non ANSI 4 bolt w/ (4) 9/16" dia. holes	GF 50
UPS 50-240/2	20-180	1-62	3	3450	2" non ANSI 4 bolt w/ (4) 9/16" dia. holes	GF 50
UPS 53-55/57 F	20-150	1-30	1-3	3450	2", 2 1/2", 3" non ANSI 4 bolt w/ (4) 5/8" dia. holes	GF 53
UPS 75-69 F	20-170	1-46	1-3	3450	3" ANSI 125# R.F.	GF 80
UPS 80-40/4	30-200	1-13	3	1750	3" ANSI 125# R.F.	GF 80
UPS 80-80/4	30-260	1-25	3	1750	3" ANSI 125# R.F.	GF 80
UPS 80-160/2	30-275	1-49	3	3450	4" ANSI 125# R.F.	GF 80
UPS 100-40/4	30-270	1-12	3	1750	4" ANSI 125# R.F.	GF 100